TORO. Count on it.

Workman® HDX Auto

FEATURES

- *Toro SpeedContr'l delivers precise ground speed during spraying and top dressing applications*

- *Two-speed transmission with high and low range*
- *Total vehicle payload of 3,295 lbs (1498 kg)**
- *Towing capacity 3,500 lbs (1591 kg)*
- *Kohler® 28hp liquid-cooled EFI gasoline engine*
- *Two-wheel and four-wheel drive options*

You asked for it, Toro delivered.

No manual clutch, no shifting, and no sacrifices. The same reliability, quality, and product features you have come to expect from Toro heavy-duty utility vehicles just got better. Toro's all new Workman HDX Auto.

The days of slipping tires as you let out the clutch are gone. The days of training new operators on how to drive a manual transmission are gone.

Powered by a 28hp Kohler® liquid-cooled EFI engine that is optimally timed with the transmission to deliver peak torque from 0-20 mph. No lack of power with this machine, climb the most difficult terrain with a load of sand and you will forget the bed is full.

Toro's proprietary SpeedContr'l™ insures precise ground speed to engine speed critical for accurate application rates with bed mounted top dressers and sprayers. Simply select the correct position on the SpeedContr'l and you are set. Put your foot to the floor and maintain consistent speed over undulating fairways and hills. Let the transmission and the engine do the work so the operator can focus on getting the job done.

*With standard suspension configuration including installed bed.

Call your Toro distributor at 1-800-803-8676

Workman® HDX Auto Specifications

	WORKMAN HDX AUTO, MODEL 07390
ENGINE	28 hp (14.9 kW) Kohler® LH775 Twin-cylinder, liquid-cooled electronic fuel injection
DISPLACEMENT	747cc
FUEL	Gasoline
COOLING	Liquid
TRANSMISSION	Variable speed transmission with forward high-low range and reverse featuring Toro SpeedContr'l™
MAXIMUM SPEED	Forward low range 11 mph (17.7 km/h), Forward high range 20 mph (32.2 km/h), Reverse 13 mph (20.9 km/h)
4WD MODEL	Fully automatic on-demand, bi-directional system. Uses dual bi-directional clutches. In event of rear tire slippage, clutches transmit power proportionally to front wheel with highest traction.
BASE MACHINE WEIGHT (INCLUDES BED)	HDX Auto 2WD: 1,905 lbs (866 kg) HDX Auto 4WD: 1,935 lbs (880 kg)
TOTAL PAYLOAD CAPACITY (INCLUDING TWO, 200LB PASSENGERS)	HDX Auto 2WD: 3,295 lbs (1498 kg) HDX Auto 4WD: 3,265 lbs (1484 kg)
CARGO BED CAPACITY (ASSUMES TWO, 200LB PASSENGERS)	HDX Auto 2WD: 2,895 lbs (1316 kg) HDX Auto 4WD: 2,865 lbs (1303 kg)
LENGTH	127.6" (324 cm) without bed; 130" (330 cm) with bed
WIDTH	64.7" (164.3 cm)
HEIGHT	75.8" (192.5 cm) to top of ROPS
CLEARANCE CIRCLE	2WD Inside = 32" (81 cm); Outside = 194" (493 cm) 4WD Inside = 100" (254 cm); Outside = 300" (726 cm)
GROUND CLEARANCE	7" (18 cm) with no load
DIFFERENTIAL LOCK	Electronic switch to engage rear differential lock
FRONT SUSPENSION	Independent suspension with dual A-frame control arms, dual coil springs and dual shock absorbers with anti-sway bar. Provides 5.75" (14.6 cm) travel.
REAR SUSPENSION	DeDion rear axle (weight carrying axle) suspension independent of transaxle with dual leaf springs and dual shock absorbers. Provides 3" (7.6 cm) travel.
BRAKES	4-wheel hydraulic disc brake system
CERTIFICATIONS	Certified to meet SAE J2258. Certified to meet ISO/DIS 21299 for ROPS. Engine meets all applicable emission standards per the manufacturer. Certified to meet the CE Machinery Directive.
WARRANTY	Two-year limited warranty. See Operator's Manual for further details.
TOW HITCH	600 lbs (272 kg) tongue weight 3,500 lbs (1587 kg) trailer weight Trailers over 1,500 lbs (680 kg) require trailer brakes

Specifications subject to change. Please contact your Toro distributor for details.

Workman® HDX Auto Accessories

	WORKMAN HDX AUTO ACCESSORIES
FULL AREA FLAT BED	Welded steel diamond plate flat bed that mounts to vehicle frame. Dimensions: 54.7 x 64.5 in (139 x 164 cm). Weight: 218 lbs (99 kg).
FULL FLAT BED SIDE KIT	Long bed side panels, front panel and tailgate with a fixed pivot.
1/3 FLAT BED	Welded steel diamond plate flat bed. Has (4) corner stake pockets for enhancing specialty mount applications. Dimensions: 21.5 x 54.7 in (55 x 139 cm). Weight: 55 lbs (25 kg)
1/3 FLAT BED STAKE SIDE KIT	Formed 14-gauge steel stake sides for use with 1/3 flat bed.
2/3 FLAT BED	Welded steel diamond plate flat bed. Dimensions: 48.1 x 54.7 in (122 x 139 cm). Weight: 161 lbs (73 kg)
2/3 FLAT BED SIDE KIT	Short bed side panels, front panel and tailgate with a fixed pivot for use with 2/3 flat bed. Optional tailgate release PN 92-1220.
FULL FLAT BED FOLD DOWN SIDE KIT	Hinged side panels, front panel and tailgate can be folded down independently for use with full flat bed. Dimensions: 64.5 x 54.7 x 11 in (164 x 139 x 28 cm) outside. 20 cu ft (.570 cu m) capacity. Weight = 109 lbs (49 kg)
HIGH FLOW HYDRAULICS KIT	Provides 8 gpm (30.3 liter) at 2000 psi hydraulic flow in a separate circuit to power certain attachments and accessories (standard on TC models).
200 GALLON SPRAYER	200 gallon (757 liter) low profile tank sprayer with diaphragm pump and detatchable control box. Three-section, 18.5 ft (5.6 m) open boom system.
VICON SPREADER	Pendulum action spreader with polyester hopper. 14.1 cu. ft. (.396 cu. m.), 750 lbs (340.5 kg) capacity. Spread width is 3 - 46 ft. (1 - 14 m).
TOPDRESSER 1800	18 cu. ft. (.504 cu. m), 1450 lbs (541 kg) capacity conveyor belt style topdresser hydraulically driven by remote hydraulics. 60 in (152 cm) spread width. Workman bed lift cylinders raise topdresser. Spring load metering gate.
TOPDRESSER 2500	25 cu. ft. (.7 cu. m) capacity conveyor belt style topdresser towed by Workman vehicle. Textured belt, oscillating axles and all wheel drive. Electrically activated hydraulic brakes.
PROPASS™ 200 TOPDRESSER	21 cu. ft. / 0.54 cu. m) struck (25 cu. ft. / 0.71 cu. m heaped) capacity spin style topdresser. Tow-behind or bed mount versions.
PRO FORCE™ DEBRIS BLOWER	Tow-behind, self-contained engine-driven debris blower operated with a hand-held wireless RF controller. Bed mount kit available.
1/3 VERTICAL LIFT	An elevating, scissor-lift work platform with 600 lb (272 kg) lift capacity that can be raised from 38 in (96.5 cm) to 98 in (249 cm). Slope indicator for safe operation. Removable over-ride key for lift controls.
HARD CAB	Deluxe hard cab, ROPS and CE certified. Vented front glass windshield, interior dome light and a 2-speed windshield wiper. Optional heater and mirrors available.
CAB SLIDING WINDOW DOOR KIT	Door kit for deluxe hard cab. Operator door has a sliding window for ventilation and ability to access exterior elements such as an identification badge security entry. Passenger door has solid window.
CAB SOLID WINDOW DOOR KIT	Door kit for deluxe hard cab. Operator and passenger doors have solid windows.
CAB REAR VIEW MIRROR KIT	Externally mounted to the cab frame, operator and passenger side rear view mirrors for enhancing all around visibility.
CANOPY	Durable, high-density polyethylene canopy with drainage outlets for moisture runoff.
FOLDING WINDSHIELD	Clear high-impact modified acrylic material with fold down capability.
BRAKE & SIGNAL KIT	Consists of turn signal lights for both corners in the front and rear of vehicle and brighter beam headlights.
WORK LIGHT KIT	Consists of (2) front facing and (1) rear facing work lights all mounted on top of ROPS bar.
ROPS SIGNAL LIGHT KIT	Consists of (2) double amber warning lights and (2) single red tail lights all for mounting on top of ROPS bar. Requires either a “Right Side” or “Left Side” light kit.
AUTOMATIC TAILGATE RELEASE	Provides automatic tailgate release when dumping from cargo bed and resets automatically upon lowering of bed. Works on full or 2/3 bed with full sides. Does not work with folding side kit.
HAND THROTTLE	Throttle and speed limit control that provides constant RPM for stationary attachments or a controlled maximum speed for applications such as spraying or spreading.
SPARK ARRESTOR	Fits onto end of tailpipe.
PLASTIC BED LINER	A rugged, weatherproof one-piece plastic liner and separate tailgate liner that will protect either a full are bed with sides or a 2/3 bed with sides.
HIGH AIR INTAKE KIT	Kit for extending the air intake system from underneath the cargo bed to a position slightly above the ROPS shield behind the passenger position of the vehicle. Recommended for dusty work applications.
REAR VIEW MIRROR KIT	A single 8 1/2” (21.6 cm) convex mirror with mounting capability on either the operator or passenger side of the vehicle.

Specifications subject to change. Please contact your Toro distributor for details.

Workman® HDX Auto Accessories (continued)

	WORKMAN HDX AUTO ACCESSORIES
2" RECEIVER HITCH KIT	Provides a 2" square receiver to enable a "drawbar" hitch.
TRAILER BRAKE WIRING KIT	Kit provides a controller which plugs into Workman vehicle and a positive wire to assist the hook up of customer supplied electric trailer brakes.
TRAILER SIGNAL WIRING KIT	Kit provides electrical wire for Workman vehicle to enable easy hook up to customer supplied trailer signal and brake lights.
REMOTE HYDRAULIC MANIFOLD KIT	Hydraulic manifold kit that provides to ability to switch hydraulics between cargo bed actuation and remote port usage via use of a operator panel mounted switch.
REMOTE HYDRAULIC FLOAT KIT	Hydraulic float kit that enables both hydraulic lifting and "float" in the down position. Required when using a Deere TC125 sweeper.
4WD MANUAL CONTROL	Allows auto 4WD to be turned off.
4 POST ROPS CANOPY KIT	Canopy for use with 4-post ROPS kit.
4 POST ROPS KIT	Connects standard 2-post ROPS to 4-post ROPS. Required with 200-gallon sprayer.
HEATER KIT	Heater for use with cab. Adjustable temperature and 2-speed fan (excludes HD).
BACK UP ALARM KIT	Provides an audible alarm when vehicle is in reverse.

©2014 The Toro Company
8111 Lyndale Ave. S.
Bloomington, MN 55420-1196
Printed in the U.S.A.

Specifications subject to change. Please contact your Toro distributor for details. Rev. 1/14